



**PROMECH**  
— W A T E R —

**BALANCE VALVES  
PRODUCT CATALOGUE**

[www.promechgroup.com](http://www.promechgroup.com)

#### STATIC BALANCE VALVES / FLANGED

SBVF-16



Dimension Range	: DN40 → DN300
Body & Bonnet	: GG-25 Cast Iron (EN GJL 250)
Disc	: GGG-40 Ductile Iron (EN GJS 400-15)
Stem	: AISI 420 Stainless Steel
Measuring Probe	: Brass (CW617N)
Handweel	: Ebonite (DN40-DN150)- Cast Iron (DN200-DN300)
Gasket	: EPDM
Connection Type	: Flanged
Max. Operating Temperature	: +120 °C
Max. Working Pressure	: PN16

#### STATIC BALANCE VALVES / THREADED

SBVT-25



Dimension Range	: DN15 → DN50
Body	: Bronze Casting
Bonnet	: CuZn40Pb2 (CW617N) Brass
Stem & Disc	: CuZn40Pb2 (CW617N) Brass
Measuring Probe	: Brass (CW617N)
Handweel	: Ebonite
Gasket	: EPDM
Connection Type	: Threaded (FF)
Max. Operating Temperature	: +120 °C
Max. Working Pressure	: PN25